



manufacturer and stockist of wire and strip

SHAPED WIRE FOR SPRINGS

Head Office

Webster & Horsfall Limited
 Hay Mills, Birmingham B25 8DW
 West Midlands, United Kingdom

Tel: +44 (0)121 772 2555 **Fax:** +44 (0)121 766 5816

E-mail: sales@websterandhorsfall.co.uk

www.websterandhorsfall.co.uk

Sales Office

Tel: +44 (0)121 772 9797 **Fax:** +44 (0)121 766 5816

DRAWN SQUARE WIRE

Hard drawn Carbon spring wire
 0.71mm – 8.0mm
 Stainless spring wire
 0.8mm – 5.53mm

Annealed Carbon and low alloy spring wire
 0.8mm – 9.5mm

ROLLED SECTION WIRE

Hard drawn Carbon and stainless steel spring wire
 (stainless by special arrangement - maximum width 4mm)

 width maximum 9.5mm thickness range 0.5mm – 3.26mm
 width minimum 1.0mm thickness range 0.4mm – 0.9mm

Oil tempered Carbon and low alloy spring steel wire (round edge only)

 width maximum 12.5mm thickness range 1.63mm – 6.35mm
 width minimum 1.27mm thickness range 0.5mm – 1.0mm

Annealed Carbon and low alloy

 width maximum 12.5mm thickness range 0.5mm – 6.35mm
 width minimum 1.0mm thickness range 0.4mm – 0.89mm

Special shapes and sections
 AI and HM rope sections, special spring wire sections. ie diamonds, hexagons and trapezoidals, can be manufactured by special arrangement, please advise us of your requirements.

